

Rexxam

Quality in vision care

from  Grafton Optical

ACCUREF K-900/R-800

Auto Ref-Keratometer / Refractometer



Proudly  Made in Japan

About Us

Rex + Max = Rexam

Rexam, which means 'the king of the kings', is a respected and reliable brand.

Rexam is a Japanese company with a celebrated 60 year history. With over 3,000 employees worldwide, Rexam manufacture a wide range of products for various industries; from factory automation, automobiles and air conditioning systems, to beer and ski boots.

Since 1986, Rexam has manufactured various high quality products for leading brands in the eye care industry, including SHIN-NIPPON. Rexam had developed and manufactured products for SHIN-NIPPON since 1993 and in 2014 the company took over the SHIN-NIPPON brand.

We will be bringing high quality ophthalmic equipment to a global market. By combining precision engineering with industry leading innovation and experience in mass production, Rexam produce unique products to support eye care specialists across the world.

Quality in vision care, we are Rexam.



1960
Foundation of Rexam

1986
Rexam started the development and manufacturing of ophthalmic devices as an OEM supplier

1993
Rexam became the main OEM partner for SHIN-NIPPON
SHIN-NIPPON

2014
Rexam acquired the SHIN-NIPPON brand
SHIN-NIPPON by **Rexam**

2018
The manufacturer brand Rexam was inaugurated
Rexam

Rexam
Quality in vision care

Proudly  Made in Japan



Classic - Compact - Ergonomic Design

Rexxam's Auto Ref-Keratometer K-900 & Auto Refractometer R-800 offer accurate and reliable objective measurement results. This classic, compact, ergonomic design ensures easy and comfortable operation to eye-care professionals in their daily practices.


- Small footprint
- WTW measurement
- (Scotopic) Pupil measurement
- IOL mode
- Minimum pupil size $\Phi 2.0$ mm
- Connectivity with Digital Refractor DR-900
- Wide measurement range

Practical and comfortable to use




Monitor - Flexible Vertical-Horizontal Tilt Angle

Monitor 30° left-horizontal tilt allows the user to measure whilst supporting the patient. The 40° vertical tilt enables the user to operate comfortably at standing or sitting positions.




IOL Mode (Colour focus indicator)

Intraocular Lens (IOL) mode allows the possibility to measure eye with implanted Intraocular lens. The Red/Green focus indicator makes alignment easy, especially where irregular reflection occurs with some implanted IOL's.



Color changes to green when focus is achieved



WTW measurement

WTW (White-to-White) corneal diameter measurement is an important factor for various ophthalmic applications such as contact lens fitting, etc.



Pupil diameter measurement

ACCUREF K-900 / R-800 have pupil size measurement functions. Pupil diameter is taken automatically during objective measurement and Scotopic Pupil Size (SPS) measurement can be taken without objective measurement.



Lateral headrest

The inward-curve design of the examination window section prevents strong light from directing to patient's eyes and minimises distraction. The headrest/chinrest sections keep the patient in comfortable position during measurement.



Capacitive touch sensor buttons

The capacitive touch sensor buttons work responsively whilst keeping the main screen clear from fingerprints, etc.



Intuitive joystick operation

The Joystick is solid and ergonomically built to ensure maximum comfort and intuitive fast operation.



Comprehensive print out

- Selective Printout in 3 different formats:
- Up to 10x REF data + KRT data
- Up to 10x REF data + KRT data (average)
- Only average REF data + KRT data

Breath shield

A dedicated breath-shield is available as an option in case of social distancing requirements. (Optional)



When all setting items are enabled

		ABCDEFGHIJKL MNOPQRSTUVWXYZ				Message Area					
		No. 00001									
		NAME 2011 11 22				14:30				Date & Time	
		VD=12									
IOL Mark	<R>	SPH	CYL	AX	PPS	Photopic Pupil Diameter					
	1	- 3.87	-0.75	172	5.4	Ref Value					
Reliability Warning Indicator	1	- 3.87	-0.75	170	5.3	Ref Value					
	R1	- 3.87	-0.62	174	5.4	Ref Representative Value					
		- 3.87	-0.75	172	5.4	Ref Representative Value					
Scotopic Pupil Diameter	SPS	7.3									
		<R>	mm	D	AX						
		R1	8.43	40.00	9						
		R2	8.21	41.12	99						
		AVE	8.32	40.62							
		CYL	-1.12	9							
		R1	8.43	40.00	10						
		R2	8.22	41.12	100						
		AVE	8.32	40.50							
		CYL	-1.12	10							
		R1	8.30	40.62	?						
		R2	8.16	41.37	92						
		AVE	8.23	41.00							
		CYL	-0.75	2							
		R1	8.31	40.62	180						
		R2	8.17	41.37	90						
		AVE	8.24	41.00							
		CYL	-0.75	180							
Residual Astigmatism	REST	-0.21 131									
		<L>	SPH	CYL	AX	PPS					
		1	- 3.75	-1.12	13	6.6					
		1	- 3.75	-1.12	15	6.6					
		1	- 3.75	-1.12	14	6.6					
		1	- 3.75	-1.12	14	6.6					
		SPS	6.9								
Near PD	PD = 65 NPD = 62 (50)										
Far PD	PD = 65 NPD = 62 (50)										
Rexxam	ACCUREF K-900										
Interpupillary Measurement Function											



			K-900	R-800
Refractive Measurement Range (Ref Measurement)	Sphere (S)	Measurement Range	-30D ~ +22D (VD=12) -22D ~ +30D (VD=0)	
		Step	0.12D, 0.25D (Switching)	
	Cylinder (C)	Measurement Range	0D ~ ±10D (VD=0)	
		Step	0.12D, 0.25D (Switching)	
		Symbol	-, +, ± (Switching)	
	Axis (A)	Measurement Range	0° ~ 180°	
		Step	1°, 5°	
Vertex Distance		0, 10, 12, 13.5, 15 mm		
Minimum Pupil Diameter Measurable		Φ2.0 mm		
Corneal Curvature Radius Measurement	Corneal Curvature Radius	Measurement Range	5.0 mm~ 10.0 mm	-
		Step	0.01 mm	-
	Corneal Refractivity	Measurement Range	33.75D ~ 67.5D (where corneal refractive index n = 1.3375)	-
		Step	0.12D, 0.25D (Switching)	-
	Degree Of Corneal Astigmatism	Measurement Range	0D ~ ±10D	-
		Step	0.12D, 0.25D (Switching)	-
		Symbol	mm, -D, +D (Switching)	-
	Axis Angle	Measurement Range	0° ~ 180°	-
Step		1°, 5°	-	
PD Measurement	Measurement Range		85mm	
	Step		1mm	
Pupil Diameter Measurement	Measurement Range		Φ2.0 mm ~ Φ8.5 mm	
	Step		0.1mm	
Measurement Time	Refractive Measurement Range		approx. 0.07 sec.	
	Corneal Curvature Radius Measurement		approx. 0.07 sec.	-
Fog Contrl	Fogging for Each Measurement (Auto) Fogging is Provided at the First Measurement Followed by Continuous Measurement (Auto-Quick)			
Monitor	5.7 inch color LCD monitor			
Printer	Thermal line printer			
Power	Power Voltage	AC 100 ~ 240 V, 50/60Hz		
	Power Consumption	60VA		
	Power Saving Function	OFF, 3, 5, 10 min. (selectable)		
Data Output	R2-232C interface			
Size	Weight	approx. 13kg		
	Dimensions	240mm(W) × 422mm(D) × 430mm(H)		
Movement Range of The Measurement Unit	Forward - Backward : ±22mm Right - Left : ±43mm Up - Down : ±17mm			
Movement Range of The Chin Rest	Up - Down : ±30mm			
Movement Range of LCD	Swivel : left 30° Vertical Tilt : up 40°			

Standard Accessories

Design and specifications are subject to change without prior notice.

- Model Eye
- Printer Roll Paper
- Chin Rest Paper
- Chin Rest Paper Pin
- Spare Fuse
- Dust Cover

Manufacturer

 Quality in vision care

Distributed by 

Unit 7 River Park Industrial Estate
 Billet Lane
 Berkhamsted
 Hertfordshire
 HP4 1HL

01923 233980
 sales@graftonoptical.com
 graftonoptical.com

Proudly  Made in Japan





 / Rexxam





